

American AVK Resilient Wedge Gate Valve Class Code/ Ref. # / Breakdown



- 03 - Small Ductile
- 18 - Combitee
- 25 - Full Wall Grey Iron
- 45 - Full Wall Ductile
- 55 - Large Diameter Ductile
- 65 - Reduced Wall Ductile
- 66 - HDPE Ends, Ductile

- 032 - 1" *
- 040 - 1.25" *
- 050 - 2"
- 063 - 2" *
- 065 - 2.5"
- 070 - 2.5" *
- 080 - 3"
- 090 - 3" *
- 100 - 4"
- 150 - 6"
- 200 - 8"
- 250 - 10"
- 300 - 12"
- 350 - 14"
- 400 - 16"
- 450 - 18"
- 500 - 20"
- 600 - 24"
- 800 - 30"

- EE - PExPE
- FF - FLxFL
- GG - GRxGR
- II - IPSxIPS
- ME - MJxPE
- MF - MJxFL
- MM - MJxMJ
- PF - POxFL
- PP - POxPO
- TT - NPTxNPT

- C - Cut-in
- F - Fitting
- H - High Pressure
- N - NRS
- O - OS&Y
- P - PIV
- T - Tapping

* For Series 03 only






SERIES 65 AWWA C515

REDUCED WALL DUCTILE

Series 65 AWWA Availability Listing

Size	FLxFL	MJxFL	MJxMJ	POxFL	POxPO
2.5"	X*				
3"	X	X	X	X	X
4"	X	X	X	X	X
6"	X	X	X	X	X
8"	X	X	X	X	X
10"	X	X	X	X	X
12"	X	X	X	X	X

* Sizes below 3" not included in AWWA Standards

Type	AVK Ref. #	Size	Weight		Price US \$		
			kg	lb			
Series 65/FFN REDUCED WALL DUCTILE FL X FL To AWWA C515 Flanged ends to ASME B 16.42 — Class 150 NRS Ductile iron 250 PSI Size 2"-12"		65-065-FFN	2.5"	17	38	875	
		65-080-FFN	3"	21	46	1,039	
		65-100-FFN	4"	28	62	1,161	
		65-150-FFN	6"	47	103	1,551	
		65-200-FFN	8"	66	146	2,425	
		65-250-FFN	10"	102	224	3,851	
		65-300-FFN	12"	141	310	4,651	
For 2" valves see Series 25 pg#17 Add \$60 for anode machining							
Series 65/MFN REDUCED WALL DUCTILE MJ X FL To AWWA C515 Mechanical joint end X Flanged end to ANSI B 16.1— Class 125 NRS Ductile iron 250 PSI Size 3"-12"						less MJ accessories	
		65-080-MFN	3"	19	42	995	
		65-100-MFN	4"	25	54	1,119	
		65-150-MFN	6"	43	95	1,495	
		65-200-MFN	8"	63	139	2,335	
		65-250-MFN	10"	90	199	3,709	
		65-300-MFN	12"	135	297	4,479	
Add \$60 for anode machining							
Series 65/MMN REDUCED WALL DUCTILE MJ X MJ To AWWA C515 To AWWA C515 Mechanical joint ends NRS Ductile iron 250 PSI Size 3"-12"						less MJ accessories	
		65-080-MMN	3"	19	42	1,049	
		65-100-MMN	4"	24	52	1,171	
		65-150-MMN	6"	42	93	1,495	
		65-200-MMN	8"	59	129	2,379	
		65-250-MMN	10"	89	195	3,709	
		65-300-MMN	12"	127	279	4,693	
For 2" valves see Series 25 pg#17 Add \$60 for anode machining							
Series 65/PFN REDUCED WALL DUCTILE PO X FL To AWWA C515 Push-on joint end (TYTON) X Flanged end to ASME B 16.42 Class 150 NRS Ductile iron 250 PSI Size 4"-12"		65-100-FFN	4"	26	58	1,181	
		65-150-FFN	6"	43	95	1,557	
		65-200-FFN	8"	65	142	2,459	
		65-250-FFN	10"	96	212	3,867	
		65-300-FFN	12"	130	287	4,757	
		Add \$60 for anode machining					
		Series 65/PPN REDUCED WALL DUCTILE PO X PO To AWWA C515 Push-on joint ends (TYTON) NRS Ductile iron 250 PSI Size 4"-12"		65-100-FFN	4"	53	117
65-150-FFN	6"			79	174	1,583	
65-200-FFN	8"			120	265	2,403	
65-250-FFN	10"			182	401	3,881	
65-300-FFN	12"			316	697	4,865	
Add \$60 for anode machining							